

“联合海工400” 固定式浮吊船

“LIAN HE HAI GONG 400” Fixed derrick crane



船舶用途

本船是一艘非自航固定式扒杆起重船，起重能力 320t，主要用于海上抢险救助、重物吊装、货物装卸及打捞沉船沉物等。

Application

LIAN HE HAI GONG 400, a non-self-propelled fixed derrick crane with lifting capacity of 320t, is mainly used for ocean emergency rescue, structure installation, cargo discharge and salvage, etc.

主要技术参数 Parameters

*船舶主尺度 Main

建造年份 Built Year	1990	起重能力 Lifting capacity	320t
船籍港 Port of Registry	厦门 Xiamen	满载排水量 Full Load Displacement	3600t
总长 Length	52.40m	营运航区 Service Area	沿海 Coastal Area
型宽 Breath	23.52m	满载吃水 Loaded Draft	3.00m
型深 Depth	4.50m	总吨/净吨 G. T. /N. T	1837/551

*主要机械设备 Machinery

起重柴油机 Engine for Lifting	2×300 kW	锚机 Anchor Winch	3×15t
发电机组 Generator	2×85 kW	锚链 Anchor chain	3×φ57×220m AM2
锚 Anchor	3×4.0t		

***生活居住区 Accommodation (24)**

单人间 Single room	4
双人间 Double room	2
四人间 Four-bedroom	4

***舱容 Tank Capacity**

淡水舱 Fresh water	218.9 m ³
燃油舱 Fuel	109.46 m ³

***航行通导设备 Navigation Equipment**

AIS	FT8700	GPS	GARMIN GPS128
甚高频 VHF	ICOM M59×2	测深仪 Echo Sounder	KODEN CVS-108

联合海工400起重机性能表

Crane of LIANHEHAIGONG 400 Characteristic as below

	主钩 Main Hook	副钩 Auxiliary Hook	小钩 Whip Hook
起重量 Lifting Capacity	160t×2	80t	5t
舷外跨距 (臂角 65°) Outreach at 65°	24.4m	29m	27m
起升高度 Lifting Height	水上 66m 66m above W.L.	77m	77m
	水下 5m 5m below W.L.	5m	5m
起升速度 Lifting speed	Avg. 4.1m/sec	Avg. 8.5m/sec	0~30m/sec

